

MODEL : M107

EURO SILENT M107



Dimensions (LxWxH) mm.(in.): 2010 x 920 x 1330 (82 x 35.5x 51.75)

Genset Models	Sound Level @ 3 feet 75% load	Sound Level @ 23 feet 75% load
JM20	78.4dB(a)	68dB(a)
JM20M	78.4dB(a)	68dB(a)
JM20U	82.7dB(a)	73dB(a)
JM20UM	82.7dB(a)	73dB(a)
JM30	78.4dB(a)	68dB(a)
JM30U	82.7dB(a)	73dB(a)
JM30UM	82.7dB(a)	73dB(a)
JM40K	77dB(a)	67dB(a)
JM40UC	80.5dB(a)	71dB(a)
KM25G	70.7dB(a)	61dB(a)
KM25GM	70.7dB(a)	61dB(a)
KM25UG	76.7dB(a)	67dB(a)
KM25UGM	76.7dB(a)	67dB(a)
TM11UC	80dB(a)	70dB(a)
TM11UCM	80dB(a)	70dB(a)

TRITON POWER

ENCLOSURES

MODEL : M107

Genset Models	Sound Level @ 3 feet 75% load	Sound Level @ 23 feet 75% load
TM16K	71.7dB(a)	62dB(a)
TM16KM	71.7dB(a)	62dB(a)
TM16UC	75dB(a)	65dB(a)
TM16UCM	75dB(a)	65dB(a)
TM20K	73.5dB(a)	64dB(a)
TM20KM	73.5dB(a)	64dB(a)
TM20UC	77dB(a)	67dB(a)
TM20UCM	77dB(a)	67dB(a)
TM30UC	80.1dB(a)	70dB(a)
TM30UCM	80.1dB(a)	70dB(a)

SPECIFICATIONS

- EURO SILENT type.
- They protect stationary and mobile generator from rain and snow.
- Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust inhibiting coat.
- High corrosion resistance : stainless bolts and rivets, anodized aluminium alloy hinges, flexible seals between body sections.
- Soundfoam 2.5 inches acoustical sound treatment
- Eye lift on the top of the enclosure fixed to the skid.
- Two large doors allow easy access to the generator set for service and monitoring purposes.
- Plexiglass window mounted on enclosure door for control viewing.
- A critical silencer is mounted inside the enclosure.
- Emergency stop button is accessible from outside enclosure.